



FASTRAK

SERIES



COMMERCIAL

FASTRAK

LIMITED WARRANTY
4 YEAR
750 HOURS

MAGNETIC TOP PIN DECK LIFT SYSTEM

Adjust the deck height between 1.5"–4.5" with your foot.

CAST DECK HANGERS

Designed to help improve durability.

EASY SERVICEABILITY

Flip-up seat pan, removable floor pan, and toolless removable pulley covers to make maintenance easy and simple.

WELDED STEEL DECK

10 GA welded fabricated steel.

SMOOTHTRAK™ STEERING

Precision control designed to help trim and maneuver easily around obstacles.

FRONT AND REAR TIE DOWNS

1.5" x 3" tubular steel fabricated frame with front and rear tie downs.

LESS CLUTTER UNDER SEAT

Provides airflow aiding in keeping transmissions cooler.

TRANSMISSIONS

Serviceable Hydro-Gear® transmissions.



FASTRAK

DECK SIZE / ENGINE

48"	22 HP*	Kawasaki® FT691
48" RD	22 HP*	Kawasaki® FT691
54"	22 HP*	Kawasaki® FT691
54" RD	22 HP*	Kawasaki® FT691
60"	24 HP*	Kawasaki® FT730

FASTRAK SDX

DECK SIZE / ENGINE

48"	22 HP*	Kawasaki® FX691
54"	22 HP*	Kawasaki® FX691
60"	23.5 HP*	Kawasaki® FX730

MORE FEATURES



HIGH-BACK SUSPENSION SEAT
High-back seat with suspension and EVC cushion designed to help take pressure off the tailbone and lower back.



COMMERCIAL-GRADE KAWASAKI FT ENGINE
Full commercial remote canister air cleaner



DUAL ROTO-MOLDED FUEL TANKS
8.5 gallon fuel capacity and dual fuel gauges.

UPGRADES FOUND ON THE FASTRAK_{SDX}



EXTRA HIGH-BACK SUSPENSION SEAT
Higher backrest and more bolstered back cushion



KAWASAKI® FX ENGINE
Full commercial remote canister air cleaner



LARGER TRANSMISSIONS
Hydro-Gear® ZT-3400™



MORE WARRANTY COVERAGE
4YR/1000 HR compared to 4YR/750 HR

ACCESSORIES

(Each sold separately)

- Mulch kit
- Dump from seat bagger (8 bushels)
- Grass bagger (2-bag powered 7.2 bushels)
- Mesh side bagger (3 bushels)
- Steel side bagger (3.5 bushels)
- Steering lever extension kit
- Flex Forks®
- Light kit
- Stripe kit
- High vacuum kit



FASTRAK®

FASTRAK SDX®

ENGINE			
Manufacturer	Kawasaki® FT series, KOHLER 7500 EFI		Kawasaki® FX series
HP	48", 48" RD, 54", 54" RD deck: 22 HP* — FT691 60" deck: 24 HP* — FT730 <small>(Per SAE J1995)</small>		48", 54" deck: 22 HP* — FX691 60" deck: 23.5 HP* — FX730 <small>(Per SAE J1995)</small>
Displacement	48", 48" RD, 54": 726 cc FT691 54", 60": 747 cc 7500 EFI 60": 726 cc FT730		Vanguard: 993 cc Kawasaki: 726 cc
Cooling	Air cooled		
Engine Warranty	3-year		
DRIVE SYSTEM			
Type	Dual hydrostatic		
Transmission	Hydro-Gear® ZT-3200		Hydro-Gear® ZT-3400
Speed	Up to 10 MPH		Up to 10 MPH
Parking Brakes	Integrated into steering levers		
DECKS			
Cutting Width	Side-discharge: 48", 54", 60" • Rear-discharge: 48", 54"		Side-discharge: 48", 54", 60"
Cutting Heights	1.5"–4.5"		
Deck Lifts	Foot operated		
Depth	5"		
Blades	3		
Blade Length	48", 48" RD: 16.50" • 54", 54" RD: 18.50" • 60" deck: 20.50"		48" deck: 16.50" • 54" deck: 18.50" • 60" deck: 20.50"
Blade Tip Speed	48", 48" RD: 18,600 • 54", 54" RD: 18,900 • 60": 18,400		48": 18,600 • 54": 18,900 • 60": 18,400
Spindles	Aluminum with 1" shafts and sealed ball bearings		
Drive	Electric PTO clutch		
Construction	Fabricated 10 GA		
Spindle Mounts	Reinforced 11 GA		
Impact/Trim Areas	11 GA formed channel with rolled edge		
CONSTRUCTION			
Frame	1.5" x 3" steel tubing		
Front Axle	Fabricated with sealed ball bearings		
Front Caster Wheels	Tapered roller bearings, grease-able		
Front Caster Forks	Fabricated 3/8" steel		
GENERAL			
Seat	High-back suspension seat		Extra high-back suspension seat
Fuel Capacity	8.5 gallons		
Cupholder	Yes		
Front Tire	13 x 6.5–6		13 x 6.5–6
Drive Tire	48", 48" RD: 23 x 9.5–10 54", 54" RD, 60": 23 x 11–10		48" 23 x 9.5–10 54", 60": 23 x 11–10
DIMENSIONS			
Weight	48" 910 LBS • 48" RD: 924 LBS • 54": 925 LBS 54" RD: 933 LBS • 60": 944 lbs		48": 910 LBS • 54": 925 LBS • 60": 944 LBS
Height	45.5" • 68.7 w/ ROPS up		48.9" • 68.7 w/ ROPS up
Length	76.7"		76.7"
Width w/ Chute Up	48": 50" • 48" RD: 48.8" • 54": 55" • 54" RD: 54.8" • 60": 61.1"		48": 50" • 54": 55" • 60": 61.1"
Tire Width	48": 47.5" • 54" & 60": 51.5"		48": 47.5" • 54" & 60": 51.5"
Trim Side	48": 0.6" • 48" RD: 0.7" • 54": 1.6" 54" RD: 1.6" • 60": 4.6"		48": 0.6" • 54": 1.6" • 60": 4.6"
PRODUCTIVITY**			
Acres Per Hour	48" deck: 3.88 • 54" deck: 4.36 • 60" deck: 4.84		48" deck, 3.88 • 54" deck: 4.36 • 60" deck: 4.84

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning, and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKŌGYŌ KABUSHIKI-KAISHA. Kohler and command Pro are registered trademarks owned by Kohler Co.

Vanguard is a registered trademark owned by Briggs & Stratton Corporation. Hydro-Gear and ZT-4400 are registered trademarks owned by Hydro-Gear Limited Partnership.

Michelin, X, and Tweel are registered trademarks owned by COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN.