



X-ONE



COMMERCIAL

X-ONE



FABRICATED FRAME FOR DURABILITY

1.5" x 3.0" steel frame making it tough and durable.

FOOT-OPERATED DECK LIFT

Easily adjust the deck height between 1"–5.5" with your foot.

RUBBER FLOOR MAT

Helps provide operator comfort.

VX™ DECK

Fabricated 7 GA steel engineered for extreme vacuum to deliver an excellent after cut appearance.

SMOOTHTRAK™ STEERING

Precision control designed to help trim and maneuver easily around obstacles without feeling unstable or jerky.

DUAL FUEL TANKS

12 gallon capacity with mechanical fuel gauges.

13M™ SEAT

High-back seat with adjustable armrests and 3-inch suspension travel range.

COMMERCIAL-GRADE TORQUE

Driven by Hydro-Gear® ZT-4400® transmissions.

COMMERCIAL-GRADE ENGINES

Kawasaki® engine options backed by 3-year limited warranties.



DECK SIZE / ENGINE

| | | |
|--------|----------|---------------------|
| 52" | 27 HP* | Kawasaki® FX860 |
| 54" RD | 27 HP* | Kawasaki® FX860 |
| 60" | 27 HP* | Kawasaki® FX860 |
| 60" RD | 27 HP* | Kawasaki® FX860 |
| 60" | 29.5 HP* | Kawasaki® FX850 EFI |
| 72" | 27 HP* | Kawasaki® FX860 |
| 72" | 29.5 HP* | Kawasaki® FX850 EFI |

MORE FEATURES



DUAL USB PORT



FABRICATED STEP TREAD



7 GA ENGINE GUARD

VX™ DECK TECHNOLOGY

Designed to draw the grass into the mower blades resulting in a crisp and clean after cut appearance.

- Made with 7 GA steel and with 7 GA wrappers
- Front edge protected by 11 GA. Formed channel with rolled edge.
- Ductile cast iron spindles with steel shaft and sealed ball bearings.
- Reinforced 7 GA stamped disc spindle mounts.



ACCESSORIES

(Each sold separately)

- Semi-pneumatic front tires
- Steering lever extension kit
- Deck rear anti-scalp wheels
- 3-bag grass catcher (12 bushels)
- BacVac bagger (10 bushels)
- Mesh side bagger (3 bushels)
- Side fabric bagger (3.5 bushels)
- Metal side bagger (3.5 bushels)
- Side aluminum bagger (3.5 bushels)
- Flex Forks®
- Mulch kit
- Light kit
- Stripe kit
- Electric deck lift
- Hitch kit
- Michelin® X® Tweel® Turf
- Michelin® X® Tweel® Caster



X-ONE®

| ENGINE | |
|---------------------|---|
| Manufacturer | Kawasaki® FX series, Kohler® Command Pro®, Vanguard® |
| HP | 52", 54" RD, 60", 60" RD 72": 27 HP* Kawasaki® FX850 60", 72": 29.5 HP* Kawasaki® FX850 EFI (Per SAE J1996) |
| Displacement | FX850, FX850 EFI: 852 cc • Command Pro®: 725 cc • Vanguard®: 810 cc |
| Cooling | Air cooled |
| Air Cleaner | Canister style |
| Engine Warranty | 3-year limited |
| DRIVE SYSTEM | |
| Type | Dual hydrostatic |
| Transmission | Hydro-Gear® ZT-4400® |
| Hydraulic Cooling | Transmission mounted fans |
| Speed | Up to 12 MPH |
| Parking Brakes | Integrated with steering levers |
| DECKS | |
| Cutting Width | Side discharge: 52", 60", 72" • Rear-discharge: 54", 60" |
| Cutting Heights | 1"–5.5" |
| Deck Lift | Foot operated |
| Depth | 5.5" |
| Blades | 3 |
| Blade Length | 52" deck: 17.86" • 54" RD deck: 18.50" 60", 60 RD deck: 20.50" • 72" deck: 23.86" |
| Blade Tip Speed | 52": 17,700 • 54" RD: 18,300 • 60", 60" RD: 18,800 • 72": 18,500 |
| Spindles | Ductile cast iron with steel shaft and sealed ball bearings |
| Drive | Electric PTO clutch |
| Construction | Fabricated 7 GA with 7 GA wrappers |
| Spindle Mounts | Reinforced 7 GA stamped disc |
| Impact/Trim Areas | Front of deck: 11 GA formed channel with rolled edge |
| CONSTRUCTION | |
| Frame | 1.5" x 3" steel tubing |
| Front Axle | Fabricated with tapered roller bearings |
| Front Caster Wheels | Tapered wheel bearings and debris cap Fabricated 1/2" steel |
| GENERAL | |
| Seat | I3M™ suspension seat |
| Fuel Capacity | Dual fuel tank w/ 12 gallon capacity |
| Cupholder | Yes |
| Front Tire | 13 x 6.5–6 |
| Drive Tire | 52", 54" RD: 24 x 9.5–12 • 60", 60" RD, 72": 24 x 12–12 |
| DIMENSIONS | |
| Weight | 52": 1285 LBS • 54" RD: 1320 LBS • 60": 1290–1395 LBS 60"(Kohler®): 1290 LBS • 60" RD: 1350 LBS • 72": 1405–1425 LBS |
| Height | 49" • 72.5 w/ ROPs |
| Length | 52": 85.5" • 54" RD: 86.9" • 60" RD: 86.5" • 72": 86.9" |
| Width w/Chute Up | 52": 55.8" • 54" RD: 55.8" • 60": 61.6" • 60" RD: 61.7" • 72" • 73.6" |
| Tire Width | 52", 54" RD: 51" • 60", 60" RD, 72": 54.5" |
| Trim Side | 52": 0.9" • 54" RD: 2.0" • 60": 5.1" • 60" RD: 3.2" • 72": 12" |
| PRODUCTIVITY** | |
| Acres Per Hour | 52": 5.52 • 54" RD: 5.73 • 60", 60" RD: 6.36 |

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning, and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JŪKŌGYŌ KABUSHIKI-KAISHA. Hydro-Gear and ZT-4400 are registered trademarks owned by Hydro-Gear Limited Partnership. Michelin, X, and Tweel are registered trademarks owned by COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN.